

PRODUCT CATALOG

Professional Wireless Security System



Table of Contents

Hubs / Range Extenders / Integration Module	01
Keypad	02
Wireless Siren	03
Indoor Motion Detector	04
Glass Break Detector / Door Sensor	05
Outdoor Detector	06
Flood Detector and Waterstop	07
Contactless Card / Tag / Wireless Key Fob	08
Smart Button / PSU / Power Relay	09



Protection of Large Premises with Complex Internal Organization

Ajax Hub is ideal for securing complex properties like business centers, factories, and multi-story villas with outbuildings, managing up to 200 devices and 25 security groups for 200 users. With a radio signal range of up to 2,000 meters and network coverage of 35 km², it enables efficient organization of staff access and zoning for large premises.

25
Security Groups

200
Users

200
Devices in the system

35 km²
Max. radio range coverage with 5 ReX



Ajax Hub 2 Plus with SIM			
	Model	Description	Price
 Hub 2 Plus Jeweller	● 72010.40.BL3	<ul style="list-style-type: none"> Ethernet, Wi-Fi, dual SIM (2G/3G/4G) Max. 6500 ft. (5570 ft. photo) range Max. 5 range extenders Max. 200 devices in 25 security groups Max. 64 scenarios Free over-the-air software updates 	<ul style="list-style-type: none"> Supports detectors with photo verification Anti-sabotage (tamper, spoof, jam, etc.) Max. 100 cameras or DVRs Max. 200 users Built in backup-battery, 15 hrs. max runtime App enabled control and setup via QR code
	○ 72011.40.WH3		
Range Extender			
	Model	Description	Price
 ReX Jeweller	● 42838.37.BL3	<ul style="list-style-type: none"> Max. 5900 ft. range to device/Hub 2 Plus 2 Ah built-in battery backup 35 hrs. max offline runtime (12 hrs. w/ ethernet) Connect via Ethernet for remote placement 	<ul style="list-style-type: none"> Anti-sabotage (tamper, spoof, jam, etc.) Free over-the-air software updates App enabled control and setup via QR code
	○ 42839.37.WH3		
 ReX 2 Jeweller	● 42840.106.BL3	<ul style="list-style-type: none"> Max. 6500 ft. range to Hub/Hub 2 Plus Max. 5570 ft. photo range to Hub/Hub 2 Plus 2 Ah built-in battery backup 35 hrs. max offline runtime (12 hrs. w/ ethernet) Connect via Ethernet for remote placement 	<ul style="list-style-type: none"> Anti-sabotage (tamper, spoof, jam, etc.) Free over-the-air software updates App enabled control and setup via QR code Extra band for dedicated photo verification devices
	○ 42841.106.WH3		
Integration Module			
	Model	Description	Price
 MultiTransmitter Jeweller	● 42829.62.BL3	<ul style="list-style-type: none"> 18 programmable physical input terminals Max. 6500 ft. to Hub 2 Plus/ReX/ReX 2 1300 ft. cable distance to wired device Support EOL/2EOL/3EOL resistance increments Max. 12 V, 7 Ah back-up battery optional 	<ul style="list-style-type: none"> 15 event types as of current OS Perfect for takeovers for legacy systems Anti-sabotage (tamper, spoof, jam, etc.) Free over-the-air software updates App enabled control and setup via QR code
	○ 42830.62.WH3		
 Transmitter Jeweller	● 42854.18.NC3	<ul style="list-style-type: none"> Single programmable physical input terminal Max. 5200 ft. to Hub 2 Plus/ReX/ReX 2 3x CR123A provides 3.3 V DC to device Perfect for third-party specialty modules 	<ul style="list-style-type: none"> 14 event types as of current OS Anti-sabotage (tamper, spoof, jam, etc.) App enabled control and setup via QR code
	○ 42854.18.NC3		



Principles of Operation

The device operates security modes when a digital code is entered on the keypad. Indication notifies of current security status, problems with detectors or breakdown of communication with the hub.

Features

Alarm button is available. It notifies of each attempt to guess the code and blocks automatically if the permissible number of entries is exceeded.



Authentication to prevent forgery






Jamming detection and communication channels encryption



Tampering alarm

Keypad

	Model	Description	Price
 <p>KeyPad Jeweller</p>	<ul style="list-style-type: none"> ● 42813.12.BL3 ○ 42814.12.WH3 	<ul style="list-style-type: none"> • Wireless touch keypad /w panic button • Max. 5500 ft. to Hub 2 Plus/ReX/ReX 2 • Max. 200 personal passcodes/duress codes • Max. 99 guest codes • Fully wireless, powered by 4x AA • Anti-sabotage (passcode guessing, tamper, etc.) • Free over-the-air software updates • App enabled control and setup via QR code 	\$70.00
 <p>KeyPad Plus Jeweller</p>	<ul style="list-style-type: none"> ● 42815.83.BL3 ○ 42816.83.WH3 	<ul style="list-style-type: none"> • Wireless touch keypad /w panic button • Max. 5500 ft. to Hub 2 Plus/ReX/ReX 2 • Max. 200 personal passcodes/duress codes • Max. 99 guest codes • Fully wireless, powered by 4x AA • Anti-sabotage (passcode guessing, tamper, etc.) • Free over-the-air software updates • App enabled control and setup via QR code • Integrated speaker with sound alerts • DESFire® EV1, EV2, ISO14443-A (13.56MHz) • Card auditing with alerts for invalid reads • Stylish branded cards and fobs available 	\$87.50
 <p>KeyPad Touchscreen Jeweller</p>	<ul style="list-style-type: none"> ● 58472.148.BL3 ○ 58473.148.WH3 	<ul style="list-style-type: none"> • Wireless touch keypad /w panic button • Max. 5500 ft. to Hub 2 Plus/ReX/ReX 2 • Max. 200 personal passcodes/duress codes • Max. 99 guest codes • 6x AA backup only, 12 V DC 0.4 A required • Anti-sabotage (passcode guessing, tamper, etc.) • 5" full touchscreen controls • Free over-the-air software updates • App enabled control and setup via QR code • Detailed reporting of alerts and issues • Management & control of system and user settings • Auto screen wakeup 	\$199.95

Reacts to Alarms in a Split Second

We have developed the Jeweller radio protocol to ensure the uninterrupted operation of all devices within the security system. The Jeweller uses time frames to synchronize communication of connected devices, authentication to eliminate forgery, and encryption to protect against data leaks. Moreover, it allows devices to operate for years from pre-installed batteries. Thanks to Jeweller, StreetSiren DoubleDeck can respond to detector alarms in 0.3 seconds, even when hub is offline.



Two-way communication at a distance of up to

1,500 meters

Siren activation triggered by alarm in

0.3 second

Adjustable ping interval from

12 second





Wireless Siren			
	Model	Description	Price
 <p>HomeSiren Jeweller</p>	<ul style="list-style-type: none"> ● 42808.11.BL3 ○ 42809.11.WH3 	<ul style="list-style-type: none"> • Adjustable volume: 80 to 98 dB (@ 1 m) • Duration adjustable, 3 s to 3 min • Max. 6500 ft. to Hub 2 Plus/ReX/ReX 2 • 2x CR123A, up to 5 years • IP50 dustproof, -10 to 40°C, up to 75%RH 	<ul style="list-style-type: none"> • Connector for external LED that can serve for alerts • Integrated LED only for armed/disarmed status • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code <p>\$46.20</p>
 <p>StreetSiren Jeweller</p>	<ul style="list-style-type: none"> ● 42844.07.BL3 ○ 42845.07.WH3 	<ul style="list-style-type: none"> • Adjustable volume: 85 to 113 dB (@ 1 m) • Duration adjustable, 3 s to 3 min • Max. 4900 ft. to Hub 2 Plus/ReX/ReX 2 • 4x CR123A, up to 5 years • 12 V DC / 1.5 A optional • IP54 weatherproof, -25 to 50°C, up to 95% RH 	<ul style="list-style-type: none"> • Integrated LED for alerts, notifications, status • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code • Honeycomb metal cover <p>\$109.20</p>
 <p>StreetSiren DoubleDeck Jeweller</p>	<ul style="list-style-type: none"> ● 42846.61.BL3 ○ 42847.61.WH3 	<ul style="list-style-type: none"> • Adjustable volume: 85 to 113 dB (@ 1 m) • Duration adjustable, 3 s to 3 min • Max. 4900 ft. to Hub 2 Plus/ReX/ReX 2 • 4x CR123A, up to 5 years • 12 V DC / 1.5 A optional • IP54 weatherproof, -25 to 50°C, up to 95% RH 	<ul style="list-style-type: none"> • Integrated LED for alerts, notifications, status • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code • Plastic brandplate sold separately • Customized Brandplate replaces metal cover <p>\$87.50</p>
 <p>Brandplate</p>	<ul style="list-style-type: none"> ● 42791.63.BL ○ 42792.63.WH 	<ul style="list-style-type: none"> • 10x Faceplate for StreetSiren DoubleDeck • Market your alarm business • Printing service available in bulk (40+ Packs) 	<p>\$56.88</p>

Photo verification

More than a photo. Faster than a video.

MotionCam Jeweller will show the actual situation from the scene even before the burglars understand that they're busted. An animated series of photos follows the instant alarm for an accurate situation appraisal. MotionCam Jeweller can only take photos in case of an alarm. The detector software architecture does not support taking a photo on demand.



Motion Detected








Alarm Raised



Evidence Captured

Indoor Motion Detector

	Model	Description	Price
 <p>PIR MotionProtect Jeweller</p>	<ul style="list-style-type: none"> ● 42822.09.BL3 ○ 42823.09.WH3 	<ul style="list-style-type: none"> • PIR detection up to 39 ft. (@ H: 88.5°, V: 80°) • Pet immunity up to 44 lbs., 19 in. • Max. 5570 ft. to Hub 2 Plus/ReX/ReX 2 • 1x CR123A 	<ul style="list-style-type: none"> • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code <p>\$51.80</p>
 <p>MotionProtect Curtain Jeweller</p>	<ul style="list-style-type: none"> ● 42824.36.BL3 ○ 42825.36.WH3 	<ul style="list-style-type: none"> • Distance adjustable line-crossing detector • PIR detection up to 49 ft. (@ H: 6°, V: 90°) • Max. 5570 ft. to Hub 2 Plus/ReX/ReX 2 • 1x CR123A 	<ul style="list-style-type: none"> • IP54 weatherproof, -10 to 40 °C, up to 95% RH • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code <p>\$46.20</p>
 <p>MotionProtect Plus Jeweller</p>	<ul style="list-style-type: none"> ● 42827.02.BL3 ○ 42828.02.WH3 	<ul style="list-style-type: none"> • 2.4 Ghz microwave sensor cuts false alarms • PIR detection up to 32 ft. (@ H: 88.5°, V: 80°) • Max. 3900 ft. to Hub 2 Plus/ReX/ReX 2 • Pet Immunity up to 44 lbs., 19 in. 	<ul style="list-style-type: none"> • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code <p>\$65.80</p>
 <p>MotionCam Jeweller</p>	<ul style="list-style-type: none"> ● 42819.23.BL3 ○ 42820.23.WH3 	<ul style="list-style-type: none"> • PIR detection up to 39 ft. (@ H: 88.5°, V: 80°) • 480p photo motion camera (@ H: 105°, V: 50°) • Pet immunity up to 44 lbs., 19 in. • Max. 5600 ft. to Hub 2 Plus/ReX 2 • 2x CR123A 	<ul style="list-style-type: none"> • IP50 dustproof, -10 to 40 °C, up to 75% RH • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code • Photo verifies motion events only <p>\$114.80</p>
 <p>MotionCam (PhOD) Jeweller</p>	<ul style="list-style-type: none"> ● 57539.120.BL3 ○ 57538.120.WH3 	<ul style="list-style-type: none"> • PIR detection up to 39 ft. (@ H: 88.5°, V: 80°) • 480p photo motion camera (@ H: 105°, V: 50°) • Pet immunity up to 44 lbs., 19 in. • Max. 5600 ft. to Hub 2 Plus/ReX 2 • 2x CR123A • IP50 dustproof, -10 to 40 °C, up to 75% RH 	<ul style="list-style-type: none"> • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code • Photo verifies motion events only • Est. 25% battery usage w/ Photo-on-Demand on • Allows a snapshot to be sent at will <p>\$126.28</p>

Glass Break Detector

Principles of Operation

Detects broken glass using an electret microphone, which registers the sound of impact against the glass and of the glass falling.

Features

Two-factor detection of broken glass prevents false alarms caused by thunder, dogs barking and noise from passing trucks.



Operates up to 7 years without battery replacement





Ignores thunder, dogs barking and noise outside the window





Detects breakage at a distance of up to 9 m

Glass Break Detector


	Model	Description	Price
 GlassProtect Jeweller	● 42804.05.BL3	<ul style="list-style-type: none"> • Electret mic glass break detection up to 29 ft. • Glass break detection @ 180° • Max. 3280 ft. to Hub 2 Plus/ReX/ReX 2 • 1x CR123A 	<ul style="list-style-type: none"> • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code
	○ 42805.05.WH3		
 CombiProtect Jeweller	● 42795.06.BL3	<ul style="list-style-type: none"> • Combines Motion and Glass Break Detection • Max. 3900 ft. to Hub 2 Plus/ReX/ReX 2 • 1x CR123A • PIR detection up to 39 ft. (@ H: 88.5°, V: 80°) • Pet immunity up to 44 lbs., 19 in. 	<ul style="list-style-type: none"> • Electret mic glass break detection up to 29 ft. • Glass break detection @ 180° • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code
	○ 42796.06.WH3		

Door Sensor

	Model	Description	Price
 DoorProtect Jeweller	● 42797.03.BL3	<ul style="list-style-type: none"> • Reed switch and 1 additional NC terminal • Max. 3900 ft. to Hub 2 Plus/ReX/ReX 2 • 1x CR123A • IP50 dustproof, -10 to 40 °C, up to 75% RH 	<ul style="list-style-type: none"> • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code
	○ 42798.03.WH3		
 DoorProtect Jeweller	● 42799.21.BL3	<ul style="list-style-type: none"> • Reed switch and 1 additional NC terminal • Max. 3900 ft. to Hub 2 Plus/ReX/ReX 2 • 1x CR123A • IP50 dustproof, -10 to 40 °C, up to 75% RH 	<ul style="list-style-type: none"> • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code • Added accelerometer to detect tilting or vibration
	○ 42800.13.WH3		

Intelligent False Alarm Filter

MotionCam Outdoor is equipped with two independent PIR sensors, the signals of which are analyzed by a two-step LISA algorithm. When both sensors detect motion, LISA performs correlation and spectral analysis of the signals, which helps to instantly distinguish real threats from interferences.








HDR Camera

IR Backlight

Series Of 2-5 Photos



Outdoor Motion Detector			
	Model	Description	Price
 <p>DualCurtain Outdoor Jeweller</p>	○ 42803.81.WH3	<ul style="list-style-type: none"> 4 height & distance adjustable PIR beams Sets up line-crossing to either side 4 PIR detection up to 49 ft. (@ H: 4.5°, V: 90°) Top sensors angle down for better detection Max. 5570 ft. to Hub 2 Plus/ReX/ReX 2 	<ul style="list-style-type: none"> 2x CR123A IP54 weatherproof, -25 to 60 °C, up to 95% RH Anti-sabotage (tamper, spoof, jam, etc.) Free over-the-air software updates App enabled control and setup via QR code
 <p>MotionCam Outdoor Jeweller</p>	○ 42821.84.WH3	<ul style="list-style-type: none"> All basic features of MotionProtect Outdoor 480p photo motion camera (@ H: 105°, V: 50°) Max. 5600 ft. to Hub 2 Plus/ReX 2 4x CR123A 	<ul style="list-style-type: none"> Photo verifies motion events only IP56 weatherproof, -25 to 60 °C, up to 95% RH
 <p>MotionProtect Outdoor Jeweller</p>	○ 42826.33.WH3	<ul style="list-style-type: none"> Dual PIR detection up to 49 ft. (@ H: 90°) Pet immunity up to 31 in. Max. 5570 ft. to Hub 2 Plus/ReX/ReX 2 2x CR123A 	<ul style="list-style-type: none"> IP55 weatherproof, -25 to 60 °C, up to 95% RH Anti-sabotage (tamper, spoof, jam, etc.) Free over-the-air software updates App enabled control and setup via QR code
 <p>MotionCam Outdoor (PhOD) Jeweller</p>	○ 57540.121.WH3	<ul style="list-style-type: none"> All features of standard MotionCam Est. +25% battery usage w/ Photo-on-Demand on Allows a snapshot to be sent at will 	\$225.75
 <p>Hood for MotionProtect Outdoor</p>	○ 42810.60.WH	<ul style="list-style-type: none"> MotionProtect Rain Cover (42826.33.WH3) 	\$8.75



Constant Control. Instand Notifications.

LeaksProtect can be placed even in hard-to-reach places. It doesn't require installation, goes years without maintenance, and works 24/7. If your washing machine leaks or a pipe breaks, the detector will react immediately and report an accident. And if the facility has an anti-flooding system, Ajax will automatically shut off water supply.

Up to **5 years** of operation from battery

Works **24/7**

IP65 housing



Against Small Leaks and Big Floods

LeaksProtect detectors can protect from flood both small apartments and commercial centres/industrial complexes. If an accident happens, informative notifications will let you know where to send the plumbers.





Up to 200 detectors in the system




Name and room of the detector location in the notification

Flood Detector and WaterStop

	Model	Description	Price
 <p>LeaksProtect Jeweller</p>	<ul style="list-style-type: none"> ● 42817.08.BL3 ○ 42818.08.WH3 	<ul style="list-style-type: none"> • 4 pairs of contacts for detecting flood • Max. 4260 ft. to Hub 2 Plus/ReX/ReX 2 • 2x AAA • IP65 Waterproof, 0 to 50 °C, up to 100% RH • Anti-sabotage (spool, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code 	\$38.42
 <p>WaterStop 3/4" (DN20) Jeweller</p>	<ul style="list-style-type: none"> ● 65150.155.BL3 ○ 65149.155.WH3 	<ul style="list-style-type: none"> • Wireless water shutoff valve for 3/4" piping • DN 20 threading, 20 mm, NTP taper, female • Max. 8.5Nm torque applied to shut off • Max. 145 PSI water pressure @ -4 to 350 °F • Max. 3600 ft. to Hub 2 Plus/ReX/ReX 2 • 4x CR123A, 12 V DC 1.8 A Optional • Anti-sabotage (tamper, spool, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code 	\$195.64


Life Quality Sensor

	Model	Description	Price
 <p>LifeQuality Jeweller</p>	<ul style="list-style-type: none"> ● 57536.135.BL3 ○ 57537.135.WH3 	<ul style="list-style-type: none"> • 32 to 122 °F (±0.36 °F), 0.18 °F pitch • 0 to 100% RH (±1.8% RH), 1% RH pitch • Measures CO₂ @ 400 to 10,000 ppm ±30 ppm (up to ±3% overall) accuracy, 1 ppm pitch • Max. 5600 ft. to Hub 2 Plus/ReX/ReX 2 • 2x CR123A • IP50 dustproof, 32 to 122 °F, up to 85% RH • Anti-sabotage (tamper, spool, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code 	\$203.00





Contactless Device



	Model	Description	Price	
	<ul style="list-style-type: none"> ● 42833.89.BL ○ 42836.89.WH 	<ul style="list-style-type: none"> • Encrypted contactless card for keypad • DESFire®, ISO 14443-A (13.56 MHz) • Fully manage credentials in the app 	<ul style="list-style-type: none"> • Max 13 hubs to a card • Compatible KeyPad Plus/KeyPad Touchscreen • Available in 3/10/100 packs 	\$13.13
Contactless Pass (3 pcs)				
	<ul style="list-style-type: none"> ● 42832.89.BL ○ 42835.89.WH 	<ul style="list-style-type: none"> • Encrypted contactless card for keypad • DESFire®, ISO 14443-A (13.56 MHz) • Fully manage credentials in the app 	<ul style="list-style-type: none"> • Max 13 hubs to a card • Compatible KeyPad Plus/KeyPad Touchscreen • Available in 3/10/100 packs 	\$40.25
Contactless Pass (10 pcs)				
	<ul style="list-style-type: none"> ● 42831.89.BL ○ 42834.89.WH 	<ul style="list-style-type: none"> • Encrypted contactless card for keypad • DESFire®, ISO 14443-A (13.56 MHz) • Fully manage credentials in the app 	<ul style="list-style-type: none"> • Max 13 hubs to a card • Compatible KeyPad Plus/KeyPad Touchscreen • Available in 3/10/100 packs 	\$355.25
Contactless Pass (100 pcs)				
	<ul style="list-style-type: none"> ● 42852.90.BL ○ 42853.90.WH 	<ul style="list-style-type: none"> • Encrypted contactless key fob for keypad • DESFire®, ISO 14443-A (13.56 MHz) • Fully manage credentials in the app 	<ul style="list-style-type: none"> • Max 13 hubs to a tag • Compatible KeyPad Plus/KeyPad Touchscreen • Available in 3/10/100 packs 	\$13.13
Contactless Tag (3 pcs)				
	<ul style="list-style-type: none"> ● 42849.90.BL ○ 42851.90.WH 	<ul style="list-style-type: none"> • Encrypted contactless key fob for keypad • DESFire®, ISO 14443-A (13.56 MHz) • Fully manage credentials in the app 	<ul style="list-style-type: none"> • Max 13 hubs to a tag • Compatible KeyPad Plus/KeyPad Touchscreen • Available in 3/10/100 packs 	\$43.75
Contactless Tag (10 pcs)				
	<ul style="list-style-type: none"> ● 42848.90.BL ○ 42850.90.WH 	<ul style="list-style-type: none"> • Encrypted contactless key fob for keypad • DESFire®, ISO 14443-A (13.56 MHz) • Fully manage credentials in the app 	<ul style="list-style-type: none"> • Max 13 hubs to a tag • Compatible KeyPad Plus/KeyPad Touchscreen • Available in 3/10/100 packs 	\$402.50
Contactless Tag (100 pcs)				
	<ul style="list-style-type: none"> ● 42842.04.BL3 ○ 42843.04.WH3 	<ul style="list-style-type: none"> • Keyfob with Arm, Disarm, Night Mode, Panic • Long press or double press mode available • Max. 4260 ft. to Hub 2 Plus/ReX/ReX 2 • 1x CR2032 	<ul style="list-style-type: none"> • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code 	\$23.80
Ajax SpaceControl Jeweller				






Smart Button

	Model	Description	Price
 <p>Button Jeweller</p>	<ul style="list-style-type: none"> ● 42793.26.BL3 ○ 42794.26.WH3 	<ul style="list-style-type: none"> • Fully programmable wireless button • Choose between panic, control, others • Long press or double press mode available • Mounting kit available • Max. 4260 ft. to Hub 2 Plus/ReX/ReX 2 	<ul style="list-style-type: none"> • 1x CR2032 • IP55 weatherproof, -10 to 40 °C, up to 75% RH • Anti-sabotage (tamper, spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code <p>\$28.00</p>
 <p>Holder for Button/Double Button</p>	<ul style="list-style-type: none"> ● 42806.82.BL ○ 42807.82.WH 	<ul style="list-style-type: none"> • Allows Button/DoubleButton to be mounted • Can be mounted upside down to be hidden 	<p>\$3.50</p>

Power Supply Unit


	Model	Description	Price
 <p>6 V PSU for Hub 2/Hub 2 Plus/ReX 2</p>	42790.78.NC	<ul style="list-style-type: none"> • Connects Hub 2 Plus/ReX 2 to external battery • Replaces PSU board in Hub 2 Plus or ReX 2 • 4.2 - 16 V DC batteries accepted • Zinc air and alkaline batteries recommended 	<p>\$17.50</p>
 <p>12 - 24 V PSU for Hub 2/Hub 2 Plus/ReX 2</p>	59580.94.NC	<ul style="list-style-type: none"> • Connects Hub 2 Plus/ReX 2 to low voltage PSU • Replaces PSU board in Hub 2 Plus or ReX 2 • Accepts 8 - 32 V DC, 1 A power sources • Not available in California 	<p>\$17.50</p>

Power Relay


	Model	Description	Price
 <p>Relay Jeweller</p>	42837.19.NC3	<ul style="list-style-type: none"> • Wireless dry contact relay (12 - 24 V DC PSUs) • NO/NC contacts allow for based responses • Allows for general automation/control via Ajax • Fits inside a standard junction box • Voltage protection: 6.5 - 36.5 V DC 	<ul style="list-style-type: none"> • Max load current: 5 A at 24 V DC • IP20 touchproof, -20 to 64 °C, up to 85% RH • Anti-sabotage (spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code <p>\$30.63</p>
 <p>WallSwitch Jeweller</p>	42855.13.BL3	<ul style="list-style-type: none"> • Wireless power relay for 110 V AC • NO/NC contacts allow for based responses • Allows for general automation/control via Ajax • Fits inside a standard junction box • Voltage protection: 92 - 132 V 	<ul style="list-style-type: none"> • Max load current and protection: 13 A • IP20 touchproof, 0 to 64 °C, up to 85% RH • Anti-sabotage (spoof, jam, etc.) • Free over-the-air software updates • App enabled control and setup via QR code <p>\$29.75</p>
 <p>DIN Holder</p>	<ul style="list-style-type: none"> ● 62964.132.BL 	<ul style="list-style-type: none"> • Bracket to fix Relay or WallSwitch on DIN rail • Toolless 	<p>\$6.30</p>

Controlled with apps

Experience flexible system management, instant notifications, and core features in one app, elevating your security and comfort to the next level. The system control point is now in your smartphone!



Ajax Security Systems



AJAX | ENS

PRODUCT CATALOG

Plainview, NY

50 Commercial St., Plainview, NY 11803
Tel: 516-870-3779

Downtown LA, CA

1113 Venice Blvd., Los Angeles, CA 90015
Tel: 213-218-2260

Miami, FL

1604 NW 84 Ave., Doral, FL 33126
Tel: 786-410-6777

College Point, NY

129-04 14th Ave., College Point, NY 11356
Tel: 718-939-2710

San Francisco, CA

41324 Christy St., Fremont, CA 94538
Tel: 510-584-9007

Chicago, IL

873 Cambridge Dr., Elk Grove Village, IL 60007
Tel: 847-584-2227

Brooklyn, NY

9017 5th Ave., Brooklyn, NY 11209
Tel: 347-507-5533

Houston, TX

1720 Townhurst Dr., Houston, TX 77043
Tel: 430-702-0999

City of Industry, CA

525 Parriott Pl., City of Industry, CA 91745
Tel: 626-961-8999

Dallas, TX

12901 Valley Branch Ln., Farmers Branch, TX 75234
Tel: 972-996-1600